


## 2 W LAN DC-DC CONVERTER

Type	V <sub>in</sub>	V <sub>out</sub>	I <sub>out</sub>
GS2T12-9S	9,5 to 15,75 V	9 V	250 mA

### DESCRIPTION

The GS2T12-9S is a 2.25W unregulated DC-DC converter designed to provide power, voltage regulation and isolation for Local Area Network (CHEAPERNET and ETHERNET) transceivers from a wide range of input voltage, according to IEEE 802.3 Standard.


Enable function, active high, is available with CMOS/TTL logic operation compatibility.



### ELECTRICAL CHARACTERISTICS (T<sub>amb.</sub> = 25° C unless otherwise specified)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V <sub>i</sub>	Input Voltage	V <sub>O</sub> = -9V I <sub>O</sub> = 0 to 250mA	9.50	12	15.75	V
V <sub>ir</sub>	Input Ripple	V <sub>i</sub> = 12V I <sub>O</sub> = 250mA		45	75	mVpp
I <sub>ir</sub>	Reflected Input Current	V <sub>i</sub> = 12V I <sub>O</sub> = 250mA		10	20	mApp
I <sub>en</sub>	Enable Input Current	V <sub>i</sub> = 9.50 to 15.75V			0.2	mA
V <sub>O</sub>	Output Voltage	V <sub>i</sub> = 9.50 to 15.75V I <sub>O</sub> = 0 to 250mA	-8.55	-9.00	-9.45	V
V <sub>or</sub>	Output Ripple Voltage	V <sub>i</sub> = 12V I <sub>O</sub> = 250mA		30	70	mVpp
V <sub>is</sub>	Isolation Voltage	Input to Output	2500			Vdc
η	Efficiency	V <sub>i</sub> = 12V I <sub>O</sub> = 250mA	68	71		%
T <sub>op</sub>	Operating Ambient Temperature Range		0		+70	°C
T <sub>stg</sub>	Storage Temperature Range		-40		+85	°C

CONNECTION DIAGRAM AND MECHANICAL DATA



Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specification mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics – All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES  
 Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands -  
 Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.