



STPS140A/U

POWER SCHOTTKY RECTIFIER

MAIN PRODUCT CHARACTERISTICS

$I_{F(AV)}$	1 A
V_{RRM}	40 V
$V_F(\text{max})$	0.5 V

FEATURES AND BENEFITS


- VERY SMALL CONDUCTION LOSSES
- NEGLIGIBLE SWITCHING LOSSES
- LOW FORWARD VOLTAGE DROP
- SURFACE MOUNTED DEVICE

DESCRIPTION

Single chip Schottky rectifier suited for Switch-mode Power Supplies and high frequency DC to DC converters.

Packaged in SMA and SMB(*), this device is intended for surface mounting and used in low voltage, high frequency inverters, free wheeling and polarity protection applications.

(*) in accordance with DO214AA and DO21AC JEDEC



ABSOLUTE RATINGS (limiting values)

Symbol	Parameter		Value	Unit	
V_{RRM}	Repetitive peak reverse voltage		40	V	
$I_{F(RMS)}$	RMS forward current		7	A	
$I_{F(AV)}$	Average forward current $\delta = 0.5$	SMA	$T_L = 130^\circ\text{C}$	1	A
		SMB	$T_L = 135^\circ\text{C}$		
I_{FSM}	Surge non repetitive forward current	$t_p = 10 \text{ ms}$ Sinusoidal	60	A	
I_{RRM}	Repetitive peak reverse current	$t_p = 2 \mu\text{s}$ $F = 1 \text{ kHz}$	1	A	
I_{RSM}	Non repetitive peak reverse current	$t_p = 100 \mu\text{s}$ square	1	A	
T_{stg}	Storage temperature range		- 65 to + 150	$^\circ\text{C}$	
T_j	Maximum junction temperature		150		
dV/dt	Critical rate of rise of reverse voltage		10000	V/ μs	

STPS140A/U

THERMAL RESISTANCES

Symbol	Parameter		Value	Unit
$R_{th(j-l)}$	Junction to lead	SMA	30	$^{\circ}\text{C}/\text{W}$
		SMB	25	

STATIC ELECTRICAL CHARACTERISTICS

Symbol	Tests Conditions	Tests Conditions	Min.	Typ.	Max.	Unit
I_R^*	Reverse leakage current	$T_j = 25^{\circ}\text{C}$	$V_R = 40\text{V}$		12	μA
		$T_j = 100^{\circ}\text{C}$		0.25	2	mA
V_F^{**}	Forward voltage drop	$T_j = 25^{\circ}\text{C}$	$I_F = 1\text{A}$		0.55	V
		$T_j = 125^{\circ}\text{C}$	$I_F = 1\text{A}$		0.43	
		$T_j = 25^{\circ}\text{C}$	$I_F = 2\text{A}$		0.65	
		$T_j = 125^{\circ}\text{C}$	$I_F = 2\text{A}$		0.53	

Pulse test : * $t_p = 5\text{ms}$, $\delta < 2\%$
 ** $t_p = 380\mu\text{s}$, $\delta < 2\%$

To evaluate the maximum conduction losses use the following equation :

$$P = 0.4 \times I_{F(AV)} + 0.10 \times I_F^2(RMS)$$

Fig. 1: Average forward power dissipation versus average forward current.




Fig. 2: Average forward current versus ambient temperature ($\delta=0.5$).




Fig. 3-1: Non repetivesurge peak forward current versus overload duration (maximum values) (SMB).




Fig. 3-2: Non repetivesurge peak forward current versus overload duration (maximum values) (SMA).




Fig. 4-1: Relative variation of thermal impedance junction to ambient versus pulse duration (SMB).




Fig. 4-2: Relative variation of thermal impedance junction to ambient versus pulse duration (SMA).




Fig. 5: Reverse leakage current versus reverse voltage applied (typical values).




Fig. 6: Junction capacitance versus reverse voltage applied (typical values)




Fig. 7: Forward voltage drop versus forward current (maximum values).




Fig. 8-1: Thermal resistance junction to ambient versus copper surface under each lead (Epoxy printed circuit board, copper thickness: 35 μm)(SMB).






Fig. 8-2: Thermal resistance junction to ambient versus copper surface under each lead (Epoxy printed circuit board, copper thickness: 35 μm)(SMA).



PACKAGE MECHANICAL DATA
SMA

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.70	0.075	0.106
A2	0.05	0.20	0.002	0.008
b	1.25	1.65	0.049	0.065
c	0.15	0.41	0.006	0.016
E	4.80	5.60	0.189	0.220
E1	3.95	4.60	0.156	0.181
D	2.25	2.95	0.089	0.116
L	0.75	1.60	0.030	0.063

FOOT PRINT (in millimeters)



■ **Marking:** S140


STPS140A/U

PACKAGE MECHANICAL DATA SMB Plastic

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.45	0.075	0.096
A2	0.05	0.20	0.002	0.008
b	1.95	2.20	0.077	0.087
c	0.15	0.41	0.006	0.016
E	5.10	5.60	0.201	0.220
E1	4.05	4.60	0.159	0.181
D	3.30	3.95	0.130	0.156
L	0.75	1.60	0.030	0.063

FOOT PRINT (in millimeters)

■ Marking: G14



Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 1999 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia
Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.