



Features

- 1.Uni-directional data transmission using plastic fiber
- 2.Signal transmission speed
:MAX. 13.2Mbps (NRZ signal)
- 3.Operating voltage :2.75 to 5.25 V
- 4.TTL and high speed C-MOS LOGIC IC compatible

Outline Dimensions



Recommended drilling as viewd from the soldering face



NOTES:

Tolerance is ±0.3mm unless otherwise noted.

Absolute Maximum Ratings

@TA=25°C

Parameter	Symbol	Rating	Unit
Supply voltage	V _{cc}	-0.5 to +7.0	V
Input voltage	V _{in}	-0.5 to V _{cc} +0.5	V
Operating temperature	T _{opr}	-20 to +70	°C
Storage temperature	T _{stg}	-30 to +80	°C
Soldering temperature ^{*1}	T _{sol}	260	°C

*1 For 5s (2 times or less)


Recommended Operating Conditions

Parameter	Symbol	MIN.	TYP.	MAX.	Unit
Operating supply voltage	V _{cc}	2.75	---	5.25	V
Operating transfer rate	T	---	---	13.2	Mbps

Electro-Optical Characteristics

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Peak emission wavelength	λ _p		630	660	690	nm
Optical power output coupling with fiber	P _c	Refer to Fig. 1	-21	-18	-15	dBm
Dissipation current	I _{cc}	Refer to Fig. 2	---	8	13	mA
High level input voltage	V _{iH}	Refer to Fig. 2	2.1	---	V _{cc}	V
Low level input voltage	V _{iL}	Refer to Fig. 2	---	---	0.8	V
Low High delay time	t _{pLH}	Refer to Fig. 3	---	100	180	ns
High Low delay time	t _{pHL}	Refer to Fig. 3	---	100	180	ns
Pulse width distortion	Δ _{tw}	Refer to Fig. 3	-15	---	+15	ns


Fig. 1 Measuring Method of Optical Output Coupling with Fiber



Notes (1) $V_{CC}=5.0\text{V}$ (State of operating)

(2) To bundle up the standard fiber optic cable, make it into a loop with the diameter $D=10\text{cm}$ or more.

Fig. 2 Measuring Method of Input Voltage and Supply Current




Input conditions and judgement method

Conditions	Judgement method
$V_{in}=2.1\text{V}$ or more	$-21\text{dBm} \leq P_c \leq -15\text{dBm}$, $I_{CC}=13\text{mA}$ or less
$V_{in}=0.8\text{V}$ or less	$P_c \leq -36\text{dBm}$, $I_{CC}=13\text{mA}$ or less

Note: $V_{CC}=5.0\text{V}$ (State of operating)

Fig.3 Measuring Method of Pulse Response



Test item

Test item	Symbol	Test condition
Low High pulse delay time	t_{PLH}	Refer to the above prescriptions
High Low pulse delay time	t_{PHL}	Refer to the above prescriptions
Pulse width distortion	Δtw	$\Delta tw = t_{PHL} - t_{PLH}$

Notes (1) The waveform write time shall be 4 seconds. But do not allow the waveform to be distorted by increasing the brightness too much.

(2) $V_{CC}=5.0$ V (State of operating)

(3) The probe for the oscilloscope must be more than 1M and less than 10pF.