

2,500 V - 10,000 V Rectifiers

100 mA - 250 mA Forward Current
200 ns Recovery Time

X25FG
X50FG
X100FG

AXIAL LEADED
HERMETICALLY SEALED




4

ELECTRICAL CHARACTERISTICS AND MAXIMUM RATINGS

Part Number	Working Reverse Voltage (V _{rwm})	Average Rectified Current (I _o)		Reverse Current @ V _{rwm} (I _r)		Forward Voltage (V _f)		1 Cycle Surge Current t _p =8.3ms (I _{fsm})	Repetitive Surge Current (I _{frm})	Reverse Recovery Time (3) (T _{rr})	Thermal Impedance θ _{J-L}			Junction Cap. @50VDC @ 1kHz (C _j)		
		55°C(1)	100°C(2)	25°C	100°C	25°C	25°C				25°C	25°C	L=000		L=.125	L=.250
		Volts	mA	mA	µA	µA	Volts				mA	Amps	Amps		ns	°C/W
X25FG	2500	250	125	1.0	20	6.0	100	15	3.0	200	5	12	21.5	4.0		
X50FG	5000	150	75	1.0	20	8.0	100	10	2.0	200	5	12	21.5	3.0		
X100FG	10000	100	50	1.0	20	13.0	100	5	1.0	200	5	12	21.5	2.0		

(1)TL=55°C L=0.375" (2)TL=100°C L=0.375" (3)I_f=125mA, I_r=250mA, I_{rr}=63mA • Op.Temp.= -65°C to +175°C Stg.Temp.= -65°C to +200°C



Part	A
X25FG X50FG X100FG	.350(8.89) MAX.



Dimensions: In. (mm) • All temperatures are ambient unless otherwise noted. • Data subject to change without notice.



VOLTAGE MULTIPLIERS INC.
8711 W. Roosevelt Ave.
Visalia, CA 93291

TEL 559-651-1402
FAX 559-651-0740
www.voltagemultipliers.com

X25FG X50FG X100FG

