


- 3-Terminal Regulators
- Output Current up to 100 mA
- No External Components
- Internal Thermal-Overload Protection
- Internal Short-Circuit Current Limiting
- Direct Replacements for Fairchild  $\mu$ A78L Series



### description

This series of fixed-voltage integrated-circuit voltage regulators is designed for a wide range of applications. These applications include on-card regulation for elimination of noise and distribution problems associated with single-point regulation. In addition, they can be used with power-pass elements to make high-current voltage regulators. One of these regulators can deliver up to 100 mA of output current. The internal limiting and thermal-shutdown features of these regulators make them essentially immune to overload. When used as a replacement for a zener diode-resistor combination, an effective improvement in output impedance can be obtained, together with lower bias current.



### electrical characteristics at specified virtual junction temperature, $V_I =$ otherwise noted)

PARAMETER	TEST CONDITIONS	T ‡				UNIT
			MIN	TYP	MAX	
Output voltage		25°C				V
	$I_O = 1 \text{ mA to } 70 \text{ mA}$	Full range				
Input voltage regulation	$V_I =$	°				
	$V_I =$					
Ripple rejection	$V_I =$ $f = 120 \text{ Hz}$	25°C				dB
Output voltage regulation	$I_O = 1 \text{ mA to } 100 \text{ mA}$	°				
	$I_O = 1 \text{ mA to } 40 \text{ mA}$					
Output noise voltage	$f = 10 \text{ Hz to } 100 \text{ kHz}$	25°C				$\mu\text{V}$
Dropout voltage		25°C				V
		25°C				
		125°C				
Bias current change	$V_I =$	range			1.5	
	$I_O = 1 \text{ mA to } 40 \text{ mA}$				0.1	

‡ Pulse-testing techniques maintain  $T_J$  as close to  $T_A$  as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33- $\mu\text{F}$  capacitor across the input and a 0.1- $\mu\text{F}$  capacitor across the output. Full range for the 78L05 is  $T_J = 0^\circ\text{C to } 70^\circ\text{C}$

---

		UNIT
Input voltage, $V_I$		V
Virtual junction temperature range, $T_J$	150	°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds	260	°C
Storage temperature range, $T_{Stg}$	-65 to 150	°C

	MIN	MAX	UNIT
Input voltage, $V_I$			
Output current, $I_O$		100	mA
Operating virtual junction temperature, $T_J$	0		°C

---