



Description

The PC3301SR combines a 33,600 bps data modem providing error control and data compression with a 14,400 bps Group 3 send-and-receive fax modem on a standard PC/104 stack-through module. The PC3301SR includes FCC Part 68 registration permitting it to be connected directly to the telephone network.

The PC3301SR uses the industry standard Hayes "AT" command set for control and configuration. This insures compatibility with virtually all software drivers and applications software designed for modem communications. Fax configuration is via Class 1 and Class 2 AT Fax commands.

Xecom brings 14 years of modem expertise to the PC/104 market. In addition to the PC3301SR, Xecom offers a complete line of Fax and Data modems for PC/104 sockets.

PC3301SR Features

- Full compatibility with Hayes "AT" modem control and configuration commands. Class 1 and Class 2 AT fax commands are used for fax control.
- Small Size 3.6" x 3.8" x 0.6"
- FCC Part 68 Registered, for direct connection to the telephone line;
- 33,600bps data transfer with fallback rates include 28,800, 19,200, 14,400, 12,000, 9600, 7200, 4800, 2400, 1200 & 300bps;
- 14,400bps Group 3 fax with fallback rates of 12000, 9600, 7200, 4800 & 2400bps;
- CMOS design includes low power Auto standby mode;
- Error control and data compression provided with MNP classes 2-5,10; V.42 and V.42bis

SPECIFICATIONS**ELECTRICAL**

- Data Rates: 300, 1200, 2400, 4800, 7200, 9600, 12,000, 14,400, 16,800, 19,200, 21,600, 24,000, 26,400, 28,800, 31,200, 33,600 bits per second;
- Modem Standards: Bell 103 and 212, CCITT V.17, V.21, V.22, V.22bis, V.27ter, V.29, V.32, V.32bis, V.34 and V.34bis;
- Group 3 Fax Rates: 14,400, 12,000, 9600, 7200, 4800 and 2400 bits per second;
- Data Transmit Level: -10 ± 1 dBm;
- Receive Sensitivity: -10 to -45 dBm
- Power Requirements: 5 Volts \pm 5%, maximum current 150 milliamps; Sleep Mode current 6 milliamps;
- FCC Part 68 Registered

SYSTEM INTERFACE

- Modem configuration and control using Hayes "AT" Command set;
- Fax configuration and control using Class 1 and Class 2 "AT" Fax Commands;
- I/O Addresses: (selected by jumpers) 3F8h (COM1), 2F8h (COM2), 3E8h (COM3), and 2E8h (COM4);
- Interrupts: (selected by jumpers) IRQ2, IRQ3, IRQ4, or IRQ7;

MECHANICAL

- Size:
Length 3.6 in. (90 mm)
Width 3.8 in. (96mm)
Height 0.6 in (15mm)
[Add .3 inches (8 mm) for stackthrough pins.]
- Weight: 3.5 oz. (100 gm)

ENVIRONMENTAL

- Operating Conditions:
Temperature - 0° to 70° C
Relative Humidity - 5% to 95% non-condensing
- Storage Temperature - -25° to 85° C
- Contact Xecom for information regarding extended temperature ranges;

ORDERING INFORMATION

When ordering, please refer to the following model numbers.

- * PC3301SR - 33,600 bps modem with MNP Classes 2-5,10; V.42, V.42bis,14,400 bps Group 3 Fax, stackthrough bus
- * PC/104CR - RJ11 phone line adapter cable