




PHASE NOISE (1 Hz BW, typical)



FEATURES

- Frequency Range: 740 - 750 MHz
- Tuning Voltage: 1-4 Vdc
- MINI-16-L - Style Package

APPLICATIONS

- Digital Radios
- Data Links
- WLANs

PERFORMANCE SPECIFICATIONS

	VALUE	UNITS
Oscillation Frequency Range	740 - 750	MHz
Phase Noise @ 10 kHz offset (1 Hz BW, typ.)	-103	dBc/Hz
Harmonic Suppression (2nd, typ.)	-8	dBc
Tuning Voltage	1-4	Vdc
Tuning Sensitivity (avg.)	23	MHz/V
Power Output	4.5±2	dBm
Load Impedance	50	Ω
Input Capacitance (max.)	50	pF
Pushing	<5	MHz/V
Pulling (14 dB Return Loss, Any Phase)	<10	MHz
Operating Temperature Range	-30 to 70	$^{\circ}\text{C}$
Package Style	MINI-16-L	

POWER SUPPLY REQUIREMENTS

Supply Voltage (Vcc, nom.)	5	Vdc
Supply Current (Icc, typ.)	17	mA

All specifications are typical unless otherwise noted and subject to change without notice.

APPLICATION NOTES

- AN-100/1 : Mounting and Grounding of VCOs
- AN-102 : Proper Output Loading of VCOs
- AN-107 : How to Solder Z-COMM VCOs

NOTES:

