




SB220 THRU SB2100 SCHOTTKY BARRIER RECTIFIER

Reverse Voltage - 20 to 100 Volts

Forward Current - 2.0 Amperes

DO-204AC



*Dimensions in inches and (millimeters)



FEATURES

- * Plastic package has Underwriters Laboratory Flammability Classifications 94V-0
- * Metal silicon junction, majority carrier conduction
- * Guardring for overvoltage protection
- * Low power loss, high efficiency
- * High current capability, low forward voltage drop
- * High surge capability
- * For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- * High temperature soldering guaranteed : 260°C / 10 seconds, 0.375" (9.5mm) lead length, 5 lbs. (2.3kg) tension

MECHANICAL DATA

Case : JEDEC DO-204AC Molded plastic body
Terminals : Plated axial leads, solderable per MIL-STD-750, Method 2026
Polarity : Color band denotes cathode end
Mounting Position : Any
Weight : 0.015 ounce, 0.4 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.	SYMBOLS	SB220	SB230	SB240	SB250	SB260	SB280	SB2100	UNITS
Maximum repetitive peak reverse voltage	VRRM	20	30	40	50	60	80	100	Volts
Maximum RMS voltage	VRMS	14	21	28	35	42	56	70	Volts
Maximum DC blocking voltage	VDC	20	30	40	50	60	80	100	Volts
Maximum average forward rectified current 0.375" (9.5mm) lead length (SEE FIG.1)	I(AV)	2.0							Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	IFSM	50							Amps
Maximum instantaneous forward voltage at 2.0 A	VF	0.55			0.70		0.85		Volts
Maximum instantaneous reverse current at rated DC blocking voltage TA=25°C TA=100°C	IR	1.0 10.0							mA
Typical thermal resistance (NOTE)	R θJA	35							°C / W
Operating junction and storage temperature range	TJ,TSTG	-50 to +150							°C

NOTES : Thermal resistance junction to lead P.C.B. mounted 0.375" (9.5mm) lead length.

RATINGS AND CHARACTERISTIC CURVES SB220 THRU SB2100

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.5 - TYPICAL REVERSE CHARACTERISTICS

